


## Kondensator AUDIO AUDIO Capacitor



### Dane Techniczne / Technical data:

Napięcie znamionowe      600VDC  
Rated voltage

Kategoria klimatyczna      25/70/21  
Climatic category

(Uwagi/Notes)

1. Wyrób spełnia wymagania Dyrektywy RoHS (2011/65/WE).

Tg kąta stratności      <0,0035 @ 1kHz  
Dissipation factor

Wymiary      zgodnie z tabelą  
Dimensions      acc. to table

This product fulfils the requirements of the RoHS Directive (2011/65/EC).

### Description:

The KPSR-01 capacitors are made on the basis of paper and polypropylene dielectric films in a specially designed configuration. The capacitor section is impregnated with the use of a unique vacuum-based technology. The capacitor electrodes consist of solid silver foil. These capacitors feature housings formed from insulating resin paper tubes, terminals made of twisted copper wire 2x0,8mm, and self-extinguishing potting compound of flammability class V0. High quality and durability of the capacitors is assured by the use of carefully selected materials, production technology, as well as testing and measuring methods.


These capacitors are designed for use in audio equipment. The design of the capacitors and used technology during the production minimize the parasitic impedance components: inductance and resistance, resulting in improved quality of sound in a given audio system.

The capacitors are subjected to a series of specific tests and measurements, including a unique test using pulses of increased current amplitude and frequency of 22kHz.

The KPSR-01 capacitors can be used in d.c. and a.c. circuits within the temperature range of their climatic category. The d.c. voltage value or a.c. voltage amplitude should not exceed the specified rated voltage.

### PRZYKŁADOWY NADRUK PRINTING LAYOUT EXAMPLE

Oznakowanie  
okładziny zewnętrznej  
- krótsze  
wyrowadzenie /  
Marking of the outer  
electrode - shorter  
terminal



Kod EPD Ordering code	$\mu\text{F}$	%	Wymiary / Dimensions	
			mm	mm
<i>KPSR01H310...</i>	0,010	<i>J - ±5%~ K - ±10%</i>	18	40
<i>KPSR01H315...</i>	0,015			
<i>KPSR01H322...</i>	0,022			
<i>KPSR01H333...</i>	0,033			
<i>KPSR01H347...</i>	0,047			
<i>KPSR01H410...</i>	0,100		20	50
<i>KPSR01H422...</i>	0,220			
<i>KPSR01H433...</i>	0,330			
<i>KPSR01H447...</i>	0,470			

Other capacitance values and terminal lengths and types can be agreed upon request.

# AUDIOMIFLEX

(+48) 509 85 30 10  
audiomiflex.pl